

# OZ

60

## Ozone generator

The OZ60 ozone generator can be used for single-dose disinfection and odor elimination in rooms with primarily dry environmental conditions where no personnel are present.

### Applications

Automotive preparation |  
Pest control | Odor elimination



**Function** The mobile OZ60 device can be individually used to eliminate odors in the air / on surfaces and for single-dose disinfection in small areas or private applications. The ozone is formed from oxygen in the ambient air using the device, without any additives. The ozone molecules react quickly with a large number of organic/non-organic compounds, neutralizing odors and disinfecting the "bad" air thoroughly and reliably.

The ozone produced is usually completely consumed by this oxidation process over a certain time and decays back to oxygen.

**Equipment** Small design; easy to handle stainless steel housing; high-quality ozone components

**Assembly/maintenance** Turnkey ready – cable length 3m

### Technical data

TYPE	OZ60 12V	OZ60 230V	OZ75
Dimensions in mm L x W x H	248 x 165 x 107	248 x 165 x 107	570 x 255 x 250
Housing material	AISI304 stainless steel		AISI304 stainless steel
Ozone components / service life	Corona board / 4000h		4x UV emitters ozone high efficiency / 10,000h
Ozone performance mg / h	6000		7500
Power in W	40	70	100
Voltage	12 V DC	230V ± 10% (50 – 60Hz)	230V ± 10% (50 – 60Hz)
Connection cable in m	3m incl. Schuko plug		3 incl. Schuko plug
Weight in kg		2.8	9
Protection class		IP54	IP54
Fan power		90m <sup>3</sup> /h	360m <sup>3</sup> /h